

Prestige

10 mm tongue/groove

Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	10 x 70 x 470 mm
Toplayer:	about 3.5 mm
Construction:	2-layer construction; Hardwood toplayer and bottomlayer made of spruce Toplayer about 3.5 mm Bottomlayer 6.5 mm
Boards/ m ² per carton:	40 pieces right-hand strips/ 40 pieces left-hand strips/ 2.63
Cartons/ m ² per pallet:	36/ 94.68
Divided top layers per carton/ minimum length (mm):	2/ 235
Weight per carton/ pallet in kg:	14/ 522
Floor heating systems:	Very well suitable
Fire behavior ¹⁾ :	Cfl-s1 depending on wood specie and surface treatment.
Content of formaldehyd ²⁾ :	E1
Content of pentachlorophenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Matt USRV 33 ⁴⁾ R9 ⁷⁾ Live Natural USRV 59 ⁴⁾ R10 ⁷⁾
Abrasion resistance:	Live Matt 70/ 1100 ³⁾ Live Matt 100 ⁴⁾
Thermal conductivity ²⁾ :	0.15 W/ (m·K)
Areal thermal resistance ⁵⁾ :	0.067 m ² · K/ W



Toplayer: Hardwood

Bottomlayer: Spruce



DOP 4658



www.blauer-engel.de/uz176



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524, ⁶⁾ according to CEN/TS 15676,

⁷⁾ according to DIN EN 51130, ⁸⁾ not valid for smoked products