



**VIVA**floors

Tegels - Tiles - Fliesen

# Tegels - Tiles - Fliesen

## Specificaties - Specifications - Technische Daten

| NL   | EN  | DU                                    |                       | Lijmversie<br>Glue down<br>Kleber           | Clickversie<br>Click (SPC)<br>Klick  |
|--|---|---------------------------------------|-----------------------|---|--|
| Specificaties                                | Specifications                                | Technische Daten                      |                       |   |  |
| Totale dikte                                 | Total Thickness                               | Gesamtstärke                          | EN 428                | 2,5 mm                                      | 6 mm<br><i>Inclusief ondervloer<br/>Subfloor included<br/>Inklusive Uterlage</i>                     |
| Dikte van de slijtlaag                       | Wear layer                                    | Nutzschicht                           | EN 429                | 0,55 mm                                     | 0,55 mm  |
| Dikte geluid-<br>dempende IXPE<br>ondervloer | Thickness<br>soundinsulating<br>IXPE underlay | Stärke trittschall<br>IXPE untergrund | -                     | -   | 1 mm   |
| Totaal gewicht                               | Total Weight                                  | Total Gewicht                         | EN 430                | 4,53 kg/m <sup>2</sup>                      | 10,15 kg/m <sup>2</sup>  |
| Toplaag                                      | Surface treatment                             | Oberflächen-<br>vergütung             | Embossed              | PUR   | PUR  |
| Afmeting                                     | Dimension                                     | Abmessung                             | EN 24342              | 45,5 x 91,1 cm                              | 45,7 x 93,5 cm   |
| Gebruikscategorie                            | Usage<br>classification                       | Klassifizierung                       | EN 685                | 23, 33, 42                                  | 23, 33, 42   |
| Clickverbinding                              | Locking System                                | Klickverbinding                       |                       |   | 2G-5G Välinge  |
| Testresultaten                               | Test Results                                  | Testergebnisse                        |                       |   |  |
| Vloerverwarming                              | Underfloor<br>heating                         | Fussbodenheizung                      | EN 12524              | Suitable<br>Max. 27 °C                      | Suitable<br>Max. 27 °C   |
| Warmte doorlaat<br>weerstand                 | Thermal<br>resistance                         | Wärmedurchlass-<br>widerstand         | EN 12667              | 0,015 m <sup>2</sup> K/W                    | 0,042 m <sup>2</sup> K/W   |
| Rolstoeltest                                 | Castor Chair                                  | Rollstuhl                             | EN 425                | Pass  | Pass   |
| Brandklasse                                  | Fire resistance                               | Brandverhalten                        | EN 13501-1            | Bfl-s1                                      | Bfl-s1   |
| Weerstand chemische<br>stoffen               | Chemical<br>resistance                        | Chemikalien-<br>beständigkeit         | EN 423                | Good  | Good   |
| Restindruk                                   | Residual<br>indentation                       | Eindruckverhalten                     | EN ISO<br>24343-1     | ≤ 0,10 mm                                   | ≤ 0,15 mm  |
| Slijptest                                    | Slip resistance                               | Rutschhemmung                         | EN 13893              | R9  | R9   |
| Krasvastheid                                 | Abrasion class                                | Verschleißgruppe                      | EN 660-2              | T   | T  |
| Geluidsabsorptie                             | Sound reduction                               | Reduzierung des<br>Trittschalls       | EN 717-2<br>ISO 10140 | 4 dB  | 19 dB EU-norm<br>5 dB NL-norm<br><i>(incl Secura LVT Click Smart<br/>ISO 10140 Delta Lin 10 dB.)</i> |
| Lichtechtheid                                | Lightfastness                                 | Lichtechtheid                         | ISO 105-<br>B02       | Pass ≥ 6                                    | Pass ≥ 6   |
| Dimensionale<br>stablieiteit                 | Dimensional<br>stability                      | Massänderung                          | EN 23999              | < 0,25%                                     | < 0,15%  |
| Afmeting                                     | Dimension                                     | Verlegemass                           | EN427                 | Pass  | Pass   |
| Toxiciteit                                   | Toxic elements<br>test                        | Toxicität                             | EN 71                 | Not toxic                                   | Not toxic  |
| Garantie                                     | Warranty                                      | Garantie                              |                       | Residential 25 years<br>Commercial 10 years | Residential 25 years<br>Commercial 10 years  |

First edition 2023 - Specifications are subject to change.



IAC Gold gecertificeerd  
IAC Gold certified  
IAC Gold zertifiziert