

# tesa® Powerstrips Waterproof Hooks S plastic white



**Product Information** 

BNR 59782

### **Product Features**

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Made from high quality plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bathtub etc.)
- Hooks reusable with tesa Powerstrips Waterproof Small

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

## **Application Fields**

How to apply:

1. Clean the surface with alcohol or silicone-free glass cleaner

2. Take the included waterproof primer tissue and wipe over the surface for bonding preperation - wait for 10 seconds minimum

- 3. Apply the Powerstrip Waterproof Small strip on the surface press for 5 seconds minimum
- 4. Disengage the base plate of the hook and stick it onto the strip press for 5 seconds minimum

5. Let the hook slide down on the base plate until it is locked

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### **Product Construction**

Oil and grease resistance

Ozone resistance

<ul><li>Type of adhesive</li><li>Holding power up to</li></ul>	synthetic rubber 1 Kg	• Hook shape	Rounded square
Properties/Performance Values			
Chemical resistance	no	Residue free removal	yes
<ul> <li>Hazard material</li> </ul>	yes	Reusable	yes
<ul> <li>Humidity resistance</li> </ul>	yes	Solvent free	yes
<ul> <li>Material</li> </ul>	PS (polystyrene)	<ul> <li>Temperature resistance</li> </ul>	Ves

UV resistant no

no

no



# tesa® Powerstrips Waterproof Hooks S plastic white

**Product Information** 

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 26/02/23 – en-US