

tesa® Powerstrips Self-Adhesive Picture Hook

Product Information

BNR 58031

Product Description

Self-adhesive and removable tesa Powerstrips Picture Hooks are the smart alternative to hang up a picture without the need to drill holes and damage the wall.

Product Features

- · Easy to mount without drilling, screws or nails
- Holds objects of up to 1 kg*
- Removable without a trace thanks to the Powerstrips® technology
- · Alternative solution to nails and screws
- · Hook reusable with tesa Powerstrips LARGE

Application Fields

How to use - Step by step 1. Clean the surface with alcohol or silicone-free glass cleaner

- 2. Apply the Powerstrip Large strip on the surface press for 5 seconds minimum
- 3. Stick the hook onto the strip press for 5 seconds minimum
- 4. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	•	Hook shape	Rectangular
•	Holding power up to	1 Kg	•	Silicone free	yes

Properties/Performance Values

•	Temperature resistance	yes	•	Ozone resistance	yes
•	Chemical resistance	no	•	Residue free removal	yes
•	Hazard material	no	•	Reusable	yes
•	Humidity resistance	no	•	Solvent free	yes
•	Material	PS (polystyrene)	•	UV resistant	no
•	Oil and grease resistance	no	•	Waterproof	no

^{*}Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials



tesa® Powerstrips Self-Adhesive Picture Hook

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.